

CE				
Declaration of Performance				
2016				
DOP NO: 67350120				
Unique identification code of the product-type	ISPOSIL 120S			
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4).	Printed on packaging			
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technic specification, as foreseen by the manufacturer	SEALANT FOR FACADE: EN-15651-1: F-EXT-INT-CC: Class 20 LM SEALANT FOR GLAZING: EN-15651-2: G-CC: Class 20 LM SEALANTS FOR SANITARY JOINTS: EN-15651-3: S: Class XS			
4. Manufacturer	ISPO France 3, rue de Bitschhoffen 67350 LA WALCK France			
5. Authorized representative	Not Relevant			
6. Systems of assessment of performance	SYSTEM 3; SYSTEM 3 FOR REACTION TO FIRE			
7. Harmonized standard	EN 15651-1 ; EN 15651-2; EN 15651-3			
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	Not Relevant			
9 Notified Body	4Ward Testing, NB 2538 has carried out the Determination of Product Type under system 3.			

Conditioning: Method A+B

Substrates: Glass

10. Declared Performance				
10	Essential Characteristic	Declared Performance	Harmonised Standard	
10.1	Reaction to fire	Class E		
10.2	Release of Chemicals	NPD		
10.3	Water Tightness & Air Tightness as determined by :		EN 15651-1:2012 - EN 15651-2:2012 - EN 15651-3:2012	
10.3.1	Resistance to flow	≤ 1.5 mm		
10.3.2	Loss of volume	≤ 10%		
10.3.3	Tensile properties at maintained extension after 4 days immersion in water	NF		



10.3.4	Adhesion/Cohesion properties at maintained extension after exposure to heat, water and UV.	NF	
10.3.5	Mould growth rating	0	EN 15051 1.2012
10.3.6	Elastic Recovery	NF	EN 15651-1:2012 EN 15651-2:2012
10.3.7	Determination of tensile properties (23°C)	≥ 0.4 MPa	EN 15651-2:2012
10.3.8	Determination of tensile properties (23°C)	≥ 0.6 MPa	EN 13031-3.2012
10.3.9	Determination of tensile properties ( -30°C)	≥ 0.9 MPa	
10.3.10	Durability	Pass	

**11.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Note: this certificate is issued electronically and is valid without signature.

ISPO France Thomas MENDLER Manager

**Disclaimer:** The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, ISPO France gives no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.