

## ISPOCLEANER 59

### DESCRIPTION

**ISPOCLEANER 59** is an organic solution of polysilanes.

### AREAS OF APPLICATIONS

**ISPOCLEANER 59** can be used as cleaning agent and adhesion promoter of PU sealants (for windshield or other applications), hybrid sealants (MS or SPUR), or silicones.

### TECHNICAL DATA

Color	Transparent, colorless
Viscosity	Extremely low (ca 1 mPa.s)
Density at 20°C	Ca 0.80
Conventional solids content (EN 827)	3 %
Application temperature	15 to 30 °C
Specific data	Drying time at 20 °C : ca. 30 s

### INSTRUCTIONS FOR USE

#### Substrate preparation:

The substrates to be assembled must be dry and dust free.

When using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer.

#### Application:

Thoroughly shake the bottle before use.

Close immediately the bottle after use because this product is very sensitive to humidity.

If **ISPOCLEANER 59** gets cloudy, do not use it anymore.

- As cleaner, **ISPOCLEANER 59** can be applied with a clean and dry cloth (not fluffy) and wiped just after evaporation of the solvent, i.e. 30 to 60 seconds after application. Then wait for a minimum drying time of 10 minutes.

- As primer, a thin and uniform film of **ISPOCLEANER 59** can be applied with a brush or a lint-free applicator pad.

After drying (10 minutes minimum), apply the sealant within a one hour deadline, proceeding according to the instructions of its technical data sheet.

### STORAGE AND SHELF LIFE

12 months in the original, hermetically sealed and unopened packaging between 0 and 30 °C

1 month after first opening in the original, hermetically sealed packaging between 0 and 30 °C



3, rue de Bitschhoffen 67350 LA WALCK – France

## PACKAGING

30, 250 and 1,000 mL bottles; 200kg drums

## SAFETY

Highly flammable and irritant. See material safety data sheet before use.

### Note:

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.